



ROTARY TILLER (Rotavators)



AGRIPAK's ROTARY TILLER is a Tractor PTO driven machine used for puddling the soil before rice transplantation, chopping and mixing of green manure, crop residues and stubbles in to the soil to make it more fertile. As a secondary tillage implement, it prepares fine to accurate seedbed in one go for sowing any type of crop. Available in 30, 36, & 42 Blades models.

SPECIFICATION:	AGM-12/30	AGM-12/36	AGM-12/42	AGM-12/48
Working Width:	1300 mm	1550 mm	1800 mm	2050 mm
Tractor HP (PTO):	30 - 45 Hp	45 - 65 Hp	65 - 80 Hp	80 Hp and above
Working Depth:	220 mm	220 mm	220 mm	220 mm
No. of Blades:	30	36	42	48
Blade Type:	Speed or Universal	Speed or Universal	Speed or Universal	Speed or Universal
Side Drive:	Gear Train	Gear Train	Gear Train	Gear Train
Rotor Speed at 540 rpm:	213	213	213	213
Safety Clutch:	Between U/J Shaft and Gearbox, Adjustable.			
Mounting:	Standard 3 Point with Cat. I pins. Mounted centrally behind the Tractor.			



AGRIPAK
(AGM Series Rotavators)
Italian Shape



AGRIPAK
(AGH Series Rotavators)
German Shape



An ISO 9001:2008 Certified Company

Due to the continuous research for the better efficiency, Agripak reserves the rights to change the specification without prior notice.