



DISC RIDGER

AGRIPAK Disc Ridger is used for develop ridges for Tobacco, Potato and Other Vegetables in the fields. The Ridger is fully adjustable for giving different accurate row widths. To obtain the correct ridge profile and retain soil flow, the good size if discs are utilized.

The Disc Ridger can also be used for earthling-up the crops sown in rows.

3 - BAR DISC RIDGER

Specification :	Model: AG - 03/2bar
Frame Width:	2.70 meter
Frame Specification:	3 bar – for offset disc mounting
No. of Discs:	4 (Disc Diameter 660 mm)
No. of Ridges:	2
Wight:	400 kg
Horse Power needed:	60 – 70 hp



1 - BAR DISC RIDGER

Specification :	Model: AG - 03/1bar
Frame Width:	2 meter
Frame Specification:	1 bar – for inline disc mounting
No. of Big Discs:	4 (Disc Diameter 660 mm)
No. of Small Discs:	2 (Disc Diameter 510 mm)
No. of Ridges:	1
Row Spacing:	Adjustable
Wight:	220 kg
Horse Power needed:	50 – 60 hp



2 - BAR DISC RIDGER

Specification :	Model: AG - 03/2bar
Frame Width:	2.70 meter
Frame Specification:	2 bar – for inline disc mounting
No. of Discs:	2 (Disc Diameter 560 mm)
No. of Ridges:	2
Row Spacing:	Adjustable
Wight:	310 kg
Horse Power needed:	50 – 60 hp



An ISO 9001:2008 Certified Company

✉ mrkt@agripakgroup.com
🌐 www.agripakgroup.com

Due to the continuous research for the better efficiency, Agripak reserves the rights to change the specification without prior notice.